

Flatbox – Technical Data



- 586, Pentium® IPC System
- AC or DC operation
- UPS
- Ethernet & XGA & EIDE Drive & CD-ROM
- Long distance LCD support



MODEL	VIPER 808	VIPER 821
SBCS	586 –133 MHz	233 MHz
CPU Cache	--	512 KB
I/O	1 parallel (Ecp/EPP), 1 Floppy, PS/2 Mouse, Keyboard, COM 1 & 2: RS 232 or RS 485	
Ethernet	10 BaseT	100 BaseT
VGA	XGA	PCI CRT / LCD XGA
Video Memory	1 MB VRAM	2 MB VRAM
Video Input	--	V-Port

- **Based on:**
half-size VIPer SBCs
- **Backplane:**
2 x ISA (1 x ISA used by SBC)
- **Extension:**
1 slot available, ISA or PC/104
- **Power Supply:**
85...264 VDC/60W
5V@6A, 12V@2A, 12V@0,5A
optional 9...18 VDC or

- **Drives:**
2,5" Harddisk EIDE (4 GB)
Flash Disk 1...170 MB capacity
- **Air Cooling:**
Without fan
- **Dimensions:**
218 x 56 x 265 (depth = ½ size)
- **Weight:**
2 kg

Headquarters

Germany
Tel: +49 8165-77-0
Fax: +49 8165-77-219

Canada
Tel: +1 450 437 5682
Fax: +1 450 437 5254

Sales Offices

Germany South-West
Tel: +49 71 56 95 87 10
Fax: +49 71 56 95 87 20

Germany West
Tel: +49 21 66 9124 70
Fax: +49 21 66 91 24 71

Austria and Europe East
Tel: +43 664 381 01 02
Fax: +43 22 39 41 15

France
Tel: +33 1 34 58 12 12
Fax: +33 1 34 58 12 00

Singapore
Tel: +65 562 94 00
Fax: +65 562 94 09

Spain
Tel: +34 91 710 20 20
Fax: +34 91 710 21 52

Switzerland
Tel: +41 17 36 4111
Fax: +41 17 36 4112

United Kingdom
Tel: +44 (0) 1606 872242
Fax: +44 (0) 7070 802176

USA East
Tel: +1 561 470 0151
Fax: +1 561 470 4983

USA West
Tel: +1 650 843 0646
Fax: +1 650 843 0646