

Rackbox 500 – Technical Data



- **19" rack system for reduced depth applications**



- **Motherboard**
Pentium® 233 MMX
2 x ISA, 3 x PCI, 1 x AGP
2 serial, 1 parallel, KB, external CD-Rom
- **3 1/2" Drive Bays for:**
3 x 3.5" devices such as: Floppy, Hard Disk
- **Floppy Disk**
3.5" 1.44 MB
- **Hard Disk**
Min. 4.0 MB EIDE
- **Video Adapter**
AGP graphicboard 8 MB VRAM
- **Additional Features**
Temperature control circuit
Power and HD active LED on front panel
Service friendly slot access with 90° tilt mechanism
- **AC Power Supply**
110/ 220 VAC 230 W
- **DC Power Supply**
24 VDC input
- **Dimensions (w x d x h)**
481 x 240 x 178 (4U) mm
- **Weight**
11 kg
- **Operating Temperature**
0° - 50° C
- **Protection class/EMV/MIL**
Front IP 65, IEC 950, EN60950, DIN VDE 0805, EN 55022 class A, CE.

Headquarters

Germany
Tel: +49 8165-77-0
Fax: +49 8165-77-219

Canada
Tel: +1 450 437 5682
Fax: +1 450 437 5254

Sales Offices

Germany South-West
Tel: +49 71 56 95 87 10
Fax: +49 71 56 95 87 20

Germany West
Tel: +49 21 66 9124 70
Fax: +49 21 66 91 24 71

Austria and Europe East
Tel: +43 664 381 01 02
Fax: +43 22 39 41 15

France
Tel: +33 1 34 58 12 12
Fax: +33 1 34 58 12 00

Singapore
Tel: +65 562 94 00
Fax: +65 562 94 09

Spain
Tel: +34 91 710 20 20
Fax: +34 91 710 21 52

Switzerland
Tel: +41 17 36 4111
Fax: +41 17 36 4112

United Kingdom
Tel: +44 (0) 1606 872242
Fax: +44 (0) 7070 802176

USA East
Tel: +1 561 470 0151
Fax: +1 561 470 4983

USA West
Tel: +1 650 843 0646
Fax: +1 650 843 0646