

Rackmon – Technical Data



- Multi-Scan Color-CRT-Monitor
- Resolution max. 1600 x 1200 pixel
- VESA®-DPMS™ Powermanagement
- Plug & Play Standards DDC1 / DDC2B
- Flexible System
- Easy to integrate



Headquarters

Germany

Tel: +49 8165-77-0
Fax: +49 8165-77-219

Canada

Tel: +1 450 437 5682
Fax: +1 450 437 5254

Sales Offices

Germany South-West

Tel: +49 71 56 95 87 10
Fax: +49 71 56 95 87 20

Germany West

Tel: +49 21 66 9124 70
Fax: +49 21 66 91 24 71

Austria and Europe East

Tel: +43 664 381 01 02
Fax: +43 22 39 41 15

France

Tel: +33 1 34 58 12 12
Fax: +33 1 34 58 12 00

Singapore

Tel: +65 562 94 00
Fax: +65 562 94 09

Spain

Tel: +34 91 710 20 20
Fax: +34 91 710 21 52

Switzerland

Tel: +41 17 36 4111
Fax: +41 17 36 4112

United Kingdom

Tel: +44 (0) 1606 872242
Fax: +44 (0) 7070 802176

USA East

Tel: +1 561 470 0151
Fax: +1 561 470 4983

USA West

Tel: +1 650 843 0646
Fax: +1 650 843 0646

CRT TUBE	RM 15	RM 17	RM 19
Resolution/ Pitch	1280 x 1024/ 0.26mm	1600 x 1200/ 0.26mm	1600 x 1200/ 0.26mm
Dimensions	19" 7HE	19" 8HE	19" 9HE
1. Body (H x W x D)	295 x 350 x 382 mm	344 x 390 x 413 mm	376 x 442 x 467 mm
2. Frontpanel (W x H)	483 x 310 mm	483 x 355 mm	483 x 399 mm
Bandwidth	80 MHz (-3dB)	135 MHz (-3dB)	135 MHz (-3dB)
H-Frequency	30 to 69 kHz	30 to 95 kHz	30 to 95 kHz
V-Frequency	50 to 120 Hz	50 to 150 Hz	50 to 150 Hz
Controlled by	analog VGA	analog VGA	analog VGA
Power Supply	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC
Power Consumption	max. 85 W	max. 120 W	max. 120 W
Active Area	250 x 185 mm ²	310 x 230 mm ²	365 x 275 mm ²
Operating Temperature	0 to +50°C	0 to +50°C	0 to +50°C
Storage Temperature	-20 to +60°C	-20 to +60°C	-20 to +60°C
Input Voltage	100 to 240 VAC	100 to 240 VAC	100 to 240 VAC
Humidity	max. 90% non condensing	max. 90% non condensing	max. 90% non condensing
Protection Class	IP 54	IP 54	IP 65
Weight	14 kg	21 kg	~ 25 kg
EMV / Standard	EN50081-2 EN50082-2	EN50081-2 EN50082-2	EN50081-2 EN50082-2